Rebel™ EMP 235ic

Dual-voltage machine for MIG, TIG, Stick Welding













Industry

- Agricultural Equipment
- Automotive
- Civil Construction
- HVAC
- Industrial and General Fabrication
- Repair and Maintenance



Introducing Rebel EMP 235ic - the next level Rebel welding machine that offers TRUE multiprocess performance in a portable package. When it comes to getting around and getting work done, Rebel EMP 235ic is second to none. It is the most mobile welder in its class and has the power and performance to crush even the most demanding jobs.

- True Multi-Process excellent performance on MIG, TIG and STICK.
- Unmatched Portability weighing in at 53 lbs. (24 kg) with dual voltage capability and 4 handle roll cage. Detach the Rebel 235ic from its cart and tackle any job around the shop or out at the job site.
- Power to Perform have the confidence with Rebel 235ic to run the full range of .035 in. (0.9 mm) wire short arc and spray transfer. Also up to .045 in. (1.2 mm) solid wire and up to .052 in. (1.4 mm) cored wire. Plus, rods up to 5/32 in. (4.0 mm) and TIG rods up to 3/16 in. (5.0 mm)
- sMIG Technology innovative "smart-MIG" feature that dynamically monitors the arc characteristics ultimately adapting to your technique resulting in a smooth, stable arc. Set wire diameter and plate thickness and you are ready to weld.

Visit **esab.com** for more information

Rebel™ EMP 235ic

| Specifications | |
|----------------------|---|
| Input Voltage | 120/230 VAC, 1 Phase, 50/60 Hz |
| Welding Output | MIG (GMAW/FCAW) 230 A / 25.5 V @ 25 % Duty Cycle (230V) MIG (GMAW/FCAW) 195 A / 23.8 V @ 40 % Duty Cycle (230V) MIG (GMAW/FCAW) 170 A / 22.5 V @ 60 % Duty Cycle (230V) MMA (SMAW) 210 A / 28.4 V @ 25 % Duty Cycle (230V) MMA (SMAW) 150 A / 26 V @ 60 % Duty Cycle (230V) TIG (GTAW) 235 A / 19.4 V @ 40 % Duty Cycle (230V) TIG (GTAW) 200 A / 18 V @ 60 % Duty Cycle (230V) |
| Wire Diameter | Mild Steel 0.6-1.0 mm (.024045 in.) Stainless Steel 0.8-1.0 mm (.030045 in.) Aluminium 0.8-1.2 mm (.030 - 3/64 in.) Flux Cored 0.8-1.2 mm (.030052 in.) |
| Max Spool Diameter | 100, 200 & 300 mm (4, 8 & 12 in.) |
| Wire Feed Speed | 2.0-17.8 m/min (60 - 700 in./min) |
| Voltage Range | 10 - 30 V |
| Max Output | 250 A |
| Max Output | 30 V |
| MCableX | 3 m 3x2,5 mm2 H07RN-F |
| Open Circuit Voltage | 90 VDC |
| Protection Class | IP23S |
| Standards | CE: IEC/EN 60974-1, 5, 7, 10, 12 & 13. RoHS |
| Supply Plug | 230 V, Schuko 16A plug |
| Voltage Tolerance | 120 V 120 V 230 V 230 V |
| Wheel System | 2-wheel |
| Weight | 24 kg (53 lb) |
| Dimensions | 686 x 292 x 495 mm (26.5 x 11.5 x 19.5 in.) |

| Ordering Information | |
|---|------------|
| Rebel EMP 235ic System | 0558012702 |
| Rebel EMP 235ic System with Cart | 0558012704 |
| Rebel EMP 235ic for MIG/MAG, MMA and Lift TIG | 0700300989 |
| REBEL EMP 235ic Kit | 1206883 |
| Rebel EMP 235ic for MIG/MAG, MMA and Lift TIG | 0734016 |
| Rebel EMP 235ic System | 614256 |

| Options & Accessories | |
|---|------------|
| TIG Foot Control, 4.6m (15 ft.) cable and 8-pin connector | W4014450 |
| Port Tweco electrode 200 (4 m), 50 mm Dinse | 0733211 |
| Pedal control (4.6 m) and 8-pin male connector | 0733206 |
| TXH 201 5/8 npt12.5FT TIG Torch Outfit | 0558102493 |
| Rebel Single Cylinder Cart | 0558102491 |
| Tweco 200A Spool Gun, 3.6 m (12 ft) | 1027-1398 |
| Tweco 200A Spool Gun, 7.6 m (25 ft) | 1027-1399 |
| Spray Master 250 MIG Gun, 15 ft. (4.5 m) | 1023-1140 |
| TXH 202 TIG Torch 4 m | 0700300857 |
| 2-wheel trolley | 0700300872 |
| External guide 1.0mm / 1.2mm (Tef / alum) | 0736669 |
| External guide 0.6mm / 0.8mm (steel) | 0736711 |
| External guide 1.0mm / 1.2mm (steel) | 0736710 |
| V-Drive Roller 0.6 / 0.8mm | 0736666 |

| Options & Accessories | |
|---|------------|
| V-Drive Roller 0.8 / 1 mm | 0736667 |
| Trailing roller U 1.0mm / 1.2mm (Alum) | 0736668 |
| Rebel car with cylinder up to 228.6mm in diameter | 0735974 |
| TXH 201 Tig Torch 3.8m (5/8 npt) | 0735975 |
| Aluminium outlet tube kit | 0464598880 |
| Torch TBi 253 PRO | 0407995 |
| Torch TBi 253 PRO-ALU | 0408188 |
| Feed Roll, U 1.0 - 1.2mm AL | 0900192 |
| Feed Roll, 0.6 - 0.8mm | 0900292 |
| Feed Roll, 0.8 - 1.0mm | 0900795 |
| Feed Roll, V-K 1.0 - 1.2mm, Knurled | 0734013 |
| Torch TBi PRO 253 Expert 5m | 0408034 |
| Cart for 1 cylinder | 0737396 |
| Kit connector trigger and gas | 0916083 |

When choosing a top-performing welding machine you need top-performing ESAB Filler Metals.

Learn more at esab.com/fillermetals today.